

Tripods and Clamp Rods

The best choice for your requirements



The key benefit of a good tripod is its stability, robustness and the torsional rigidity. With this, durability is not the only argument for the original tripod made by Leica Geosystems. Other substantial benefits are the height stability under load and the minimal horizontal drift. Also not to be underestimated are advantages such as long life, optimal vibration dampening, water resistance, outstanding behaviour in solar radiation and their weight in relation to load-bearing capacity.



Leica CLR290 Clamp Rod*

- For step less positioning of lasers at different heights up to 2.90m
- Universal mounting platform for Leica line and rotating lasers
- Easy to be fixed e.g. between floor and ceiling

Art. No. 761 762

*(not available in the US)



Leica TRI 70 Tripod

- Small and handy tripod for everyday use
- Aluminium tripod with easy fine adjustment
- Bubble level
- ¼" screw on a stable and turnable head plate
- Transportation length: 0.45m
- Weight: 1.4kg
- Working height from 0.40m to 1.15m (including screw-out central pillar)

Art. No. 794 963



Leica TRI 100 Tripod

- Aluminium tripod with easy fine adjustment
- Robust tilt head
- Bubble level
- ¼" fixing screw on removable head plate
- Flip levers for easy adjustment
- Weight: 2.4 kg
- Working height from 0.70m to 1.72m

Art. No. 757 938



Leica TRI 200 Tripod - light duty construction tripod

- Aluminium tripod
- Bubble level
- ¼" fixing screw on
- Flip levers for easy adjustment
- Weight: 1.8 kg
- Working height from 0.75m to 1.15m

Art. No. 828 426



Leica CTP106-1 Flat-Head Aluminium Tripod with side Screws

- Triangular flat-head
- 5/8 x 11 fixing screw with hook for plumb bob
- Shoulder and leg retaining strap
- Transportation length: 1.10m
- Weight: 4.6kg
- Working height from 0.85m to 1.60m

Art. No. 789 913



Leica CET103 Crank-head Tripod

- Quality aluminium tripod with quick-release clamps
- Bubble level and shoulder strap
- Transportation length: 1.12m
- Weight: 4.6kg
- Working height from 0.84m to 2.46m (including screw-out central pillar)

Art. No. 768 033



Leica CTP104D-1 Dome-Head Tripod

- Dome-head
- 5/8 x 11 fixing screw with hook for plumb bob
- Shoulder and leg retaining strap
- Switch between rubber feet and spikes
- Chain for sliding and floor protection
- Transportation length: 1.10m
- Weight: 4.99kg
- Working height from 0.85m to 1.60m

Art. No. 790 226



CET300 Aluminium Elevator Tripod

- Professional, multifunctional aluminium elevator tripod
- Fast clamps
- Circular bubble
- Extendible centre column
- mm-scale
- Exchangeable rubber feet
- Transportation length: 1.32m
- Weight: 8.75kg
- Working height from 0.85m to 3.02m

Art. No. 790 228