

Leica Rod Eye Series

Data sheet



Laser receivers quickly and easily detect laser planes when the laser beam is not visible. Not only detecting the laser beam, they maximise performance of your Rugby laser and any construction laser on site. Work conveniently with Rugby lasers and Rod Eye receivers even at very long distances.

BENEFITS

- The most complete and professional receiver portfolio for all your general construction and interior applications
- CLC Combo+ - Receiver and Remote combined in one device with backlight
- Save time and work conveniently with offset and adjustable sensor window thanks to the features in the Combo+
- Combo+, Rod Eye 140 and 160 anti-strobe feature assures highest detection reliability by rejecting strobe light
- Designed to last - IP 67 protection on all our receivers
- Very fine detection accuracy (bandwidth) when the highest accuracy is required

Leica Rod Eye Series

The professional's choice



Technical Data	Rod Eye 120G Basic	Rod Eye 120 Basic	Rod Eye 140 Classic	Rod Eye 160 Digital	CLC Combo+ receiver-remote
Anti-strobe	-	-	✓	✓	✓
Smart Targeting / Smart Lock	-	-	-	-	✓
Working diameter (laser dependent)	400 m	900 m	1,350 m	1,350 m	1,350 m
Detection window	70 mm		120 mm		
Adjustable detection window	-	-	-	-	✓
Off Set function	-	-	-	-	✓
Digital readout / height	✓ / 70 mm	-	-	✓ / 90 mm	✓ / 90 mm
Digital readout / units	mm, cm, in, frac, ft	-	-	mm, cm, in, frac, ft	
Detectable spectrum	500 nm to 570 nm		600 nm to 800 nm		
Automatic shutoff	10 minutes				
Audio volumes	High / Low / Off			High / Med / Low / Off	
Arrow display	11 channels	9 channels	9 channels	15 channels	
Backlight					✓
Detection accuracies	Fine ± 1 mm Medium ± 2 mm Coarse ± 3 mm	Fine ± 1 mm Medium ± 2 mm Coarse ± 3 mm	Fine ± 1 mm Medium ± 2 mm Coarse ± 3 mm	Very Fine ± 0.5 mm Fine ± 1 mm Medium ± 2 mm Coarse ± 3 mm Very Coarse ± 5 mm	Very Fine ± 0.5 mm Fine ± 1 mm Medium ± 2 mm Coarse ± 5 mm
Protection class (splash /dust proof)	IP67				
Battery type / life	2x AA / 50+ hours				Li-Ion rechargeable
Dimensions (HWD)	173 x 76 x 29 mm				205 x 86 x 32 mm
Operating temperature	-20°C to +50°C				
Part number	844745 Rod Eye 120G Green Receiver w/Bracket	789922 Rod Eye 120 Basic Receiver w/Bracket	789923 Rod Eye 140 Classic Receiver w/Bracket	789924 Rod Eye 160 Digital Receiver w/Bracket	986299 CLC Combo+ receiver-remote [1] w/Bracket

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland - Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2024. 852694en - 08.24

Leica Geosystems AG
leica-geosystems.com



© 2024 Hexagon AB and/or its subsidiaries and affiliates. Leica Geosystems is part of Hexagon. All rights reserved.

- when it has to be **right**

Leica
Geosystems