

Leica TS13

Data sheet



Sometimes you need your instrument to grow with your projects. The **Leica TS13** empowers you to start with two-person mode and upgrade the instrument gradually to a robotic total station. You decide when to upgrade it – you can choose a different **keyboard**, add **lock** to follow a moving target or include **robotic capabilities** with **SpeedSearch** and controller **connectivity** via a radio handle. The TS13 comes with **AutoHeight**, helping you to setup your instrument error-free.

LEICA TS13 TOTAL STATION: COLLECT IT.

- **Efficient data collection for mapping projects:** measurements, adjustments, and computations – all supported by powerful coding and linework routines.
- **Easy-to-use and data-centric field software:** efficient data collection, management, visualisation, import and export.
- **Upgradeable total station for measurement and layout tasks:** starting with two-person, scalable to one-person operation.
- **Accurate and effective stakeout and construction measurements:** automated routines for both two-person and one-person design data layout, as-built checks, and BIM tasks.

leica-geosystems.com



- when it has to be **right**

Leica
Geosystems

Leica TS13 Total Station

Basic variant



ANGLE MEASUREMENT

Accuracy ¹ Hz and V	■ Absolute, continuous, diametrical	1" (0.3 mgon), 2" (0.6 mgon), 3" (1 mgon), 5" (1.5 mgon)
--------------------------------	-------------------------------------	--

DISTANCE MEASUREMENT

Range ²	■ Prism (GPR1, GPH1P) ³ ■ Non-Prism / Any surface ⁴	0.9 m to 3,500 m R500: 0.9 m to >500 m R1000: 0.9 m to >1,000 m
--------------------	--	---

Accuracy / Measurement time	■ Single (prism) ^{2,5} ■ Single (prism fast) ^{2,5} ■ Single (any surface) ^{2,4,5,6}	1 mm + 1.5 ppm / typically 2.4 s 2 mm + 1.5 ppm / typically 1.5 s ¹⁰ 2 mm + 2 ppm / typically 2 s ⁹
-----------------------------	--	---

Laser dot size	At 50m	8 mm x 20 mm
----------------	--------	--------------

Measurement technology	System analyser	Coaxial, visible red laser
------------------------	-----------------	----------------------------

AUTOMATIC AIMING - ATR

Target aiming range ²	■ Circular prism (GPR1, GPH1P) ■ 360° prism (GRZ4, GRZ122)	■ 1,000 m ■ 800 m
----------------------------------	---	----------------------

Accuracy ^{1,2} / Measurement time	ATR angle accuracy Hz, V	1" (0.3 mgon), 2" (0.6 mgon), 3" (1 mgon), 5" (1.5 mgon) / typically 3-4 s
--	--------------------------	--

GUIDE LIGHT (EGL)

Working range / Accuracy		5 - 150 m / typically 5 cm @ 100 m
--------------------------	--	------------------------------------

GENERAL

Processor	TI OMAP4430 1 GHz Dual-core ARM® Cortex™- A9 MPCore™	
-----------	--	--

AutoHeight module for automatic instrument height measurement	■ Distance accuracy ■ Distance range	1.0 mm (1 Sigma) 0.7 m to 2.7 m
---	---	------------------------------------

Power management	Exchangeable Lithium-Ion battery	Operating time up to 8 h
------------------	----------------------------------	--------------------------

Field software	Leica Captivate with apps	Running on field controller
----------------	---------------------------	-----------------------------

Data storage	■ Internal memory 2 GB ■ SD card 1 GB or 8 GB	On field controller
--------------	--	---------------------

Interfaces	RS232, USB, Bluetooth®, WLAN	
------------	------------------------------	--

Weight	Total station including battery	5.0 kg
--------	---------------------------------	--------

Environmental specifications	■ Working temperature range ■ Dust / Water (IEC 60529) / Humidity	■ -20°C to +50°C ■ IP55 / 95%, non-condensing
------------------------------	--	--

Upgrades⁷



KEYBOARD DISPLAY UNIT (Optional)

Keyboard with display	Face I and face II optional	5" (inch), WVGA, colour, touch 25 keys, illumination
-----------------------	-----------------------------	--

Field software	Leica Captivate including apps	Running on TS13 instrument
----------------	--------------------------------	----------------------------

Data storage	Internal memory 2 GB SD card 1 GB or 8 GB	On TS13 instrument
--------------	--	--------------------

Weight	Total station including battery	5.3 kg
--------	---------------------------------	--------

TARGET LOCK (Optional)

Target locking range ²	■ Circular prism (GPR1, GPH1P) ■ 360° prism (GRZ4, GRZ122)	■ 800 m ■ 600 m
-----------------------------------	---	--------------------

ROBOTIC SURVEYING including PRISM FAST SEARCH (Optional)¹¹

SpeedSearch range / Search time	360° prism (GRZ4, GRZ122)	300 m / Typically 7 s
---------------------------------	---------------------------	-----------------------

Robotic range with long-range Bluetooth ^{®8}	To CS20 internal long-range Bluetooth [®] To CTR20 expansion pack	500 m 1,000 m
---	---	------------------

¹ Standard deviation ISO 17123-3

² Overcast, no haze, visibility about 40 km, no heat shimmer

³ 0.9 m to 2,000 m for 360° prisms (GRZ4, GRZ122)

⁴ Object in shade, sky overcast, Kodak Gray Card (90% reflective)

⁵ Standard deviation ISO 17123-4

⁶ Distance > 500 m: Accuracy 4 mm + 2 ppm, Measurement time typically 6 s

⁷ Initial or after sales, independent from each other

⁸ Under good radio conditions

⁹ Up to 50 m, max. measurement time 15 s for full range

¹⁰ Initial measurement time typically 2 s

¹¹ Available also without prism fast search



Laser radiation, avoid direct eye exposure.
Class 3R laser product in accordance with IEC 60825-1:2014.

The Bluetooth® trademarks are owned by Bluetooth SIG, Inc. Windows is a registered trademark of Microsoft Corporation. Other trademarks and trade names are those of their respective owners. Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. Printed in Switzerland - 2020. Leica Geosystems AG is part of Hexagon AB. 929650en - 11.20



Integrate with LOC8 - Lock & Locate

For more information visit: leica-geosystems.com/LOC8

Leica Geosystems AG
Heinrich-Wild-Strasse
9435 Heerbrugg, Switzerland
+41 71 727 31 31

- when it has to be **right**

Leica
Geosystems