

Getac

Rugged Mobile Computing Solutions

ZX70

Fully Rugged Tablet



- 7" LumiBond® Display Sunlight Readable Technology and Glove-enabled Capacitive Touchscreen
- 6 Feet Drop , MIL-STD-810G and IP67 Certified
- Optional Barcode Reader and RFID Reader
- Optional 4G LTE WWAN
- High Sensitivity GPS



Office Dock



Vehicle Dock





Specifications

Operating System	Android 6.0	Security Feature	Optional Contactless RFID/NFC combo reader ⁱⁱ Optional Barcode reader Optional UHF RFID reader ⁱⁱⁱ
Mobile Computing Platform	Intel® Atom™ x5-Z8350 Processor 1.44GHz, burst up to 1.92 GHz -2MB Cache	Power	AC adapter (24W, 100-240VAC, 50 / 60Hz) Li-Ion battery (3.8V, 8400mAh)
VGA Controller	Intel® HD Graphics	Dimension (W x D x H) & Weight	218 x 142 x 27 mm 780g ^{iv}
Display	7" IPS TFT LCD HD (1280 x 720) LumiBond® display with Getac sunlight readable technology Capacitive touchscreen with glove on	Rugged Feature	MIL-STD-810G certified and IP67 certified 6 feet drop resistant Vibration & drop resistant e-Mark certified for vehicle usage Optional ANSI/ISA 12.12.01
Storage & Memory	2GB LPDDR3 expandable to 4GB eMMC 32GB / 64GB	Environmental Specification	Temperature ^v - Operating: -21°C to 60°C - Storage: -40°C to 71°C Humidity: - 95% RH, non-condensing
Keyboard	4 tablet buttons (Power, Barcode Launch Button, Volume Up, Volume Down)	Accessories	Carry bag AC adapter (24W; 12V/2A, 100-240VAC; 50 / 60 Hz) Vehicle adapter (60W, 11-16VDC and 22-32VDC) Capacitive stylus Rotating Hand Strap with Kick Stand and Stylus Holder Office dock Vehicle dock USB to RS232 converter cable Docking connector to HDMI converter cable Protection film Shoulder Strap Wrist Strap
Pointing Device	Touchscreen - Capacitive multi-touch screen		
I/O Interface	FHD webcam x 1 8M pixels auto focus rear camera x 1 MicroUSB 2.0 (Client) x 1 USB 2.0 (Host) x 1 Docking connector (Pogo/JAE) DC in Jack x 1 MicroSD x 1 Optional RF antenna pass-through for GPS and WWAN		
Communication Interface	Wi-Fi 802.11 n Bluetooth (v4.0) ⁱ Dedicated GPS Optional 4G LTE mobile broadband		
Software	Getac Settings, Google Chrome, Gmail, Google+, Google Maps, Google Play Music, Google Play Movies, Google Play Books, Google Play Newsstand, Google Play Games, Google Drive, YouTube, Google Plus Photos, Hangouts		

Docking solutions

	USB Host	USB Client	HDMI	Audio Output	Speaker	LAN	RS232	DC in Jack	RF Pass through
Getac Office dock (JAE connector)	2	1	1	1	N/A	1	N/A	1	N/A
Getac Office dock (Pogo pin)	2	N/A	N/A	1	N/A	1	N/A	1	N/A
Getac Vehicle dock (JAE connector)	2	N/A	1	1	1	1	1	1	2 (WWAN, GPS)
Getac Vehicle dock (Pogo pin)	2	N/A	N/A	1	1	1	1	1	2 (WWAN, GPS)

ⁱ Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
ⁱⁱ 13.56MHz Contactless RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
ⁱⁱⁱ UHF RFID reader is mutually exclusive with 4G LTE or Barcode reader.
^{iv} Weight and dimensions vary from configurations and optional accessories.
^v Tested by a national independent third party test lab following MIL-STD-810G.



Getac UK Ltd

Mitac House, Nedge Hill, Telford, Shropshire, TF3 3AH, UK

Tel: +44 (0) 1952 207 222
 Email: Sales-Getac-UK@getac.com
 www.getac.com

