

Leica GM30

Ready for today and tomorrow

Monitoring
Solutions



All-in-one-GNSS monitoring receiver

The GM30 is designed for continuous operation and a wide range of monitoring scenarios. It is packed with full feature onboard software including Site Monitor, Leica VADASE, data logging and FTP push. With low energy consumption, highly redundant communication capabilities and designed to withstand challenging environment conditions, this rugged receiver is ready for any challenge.



High-end GNSS technology

Exceeding GNSS signal needs today and tomorrow by supplying 555 GNSS channels, the GM30 monitoring receiver is future-proof, reliably delivering the highest quality results 24/7. With the support of all available and future GNSS signals, and with SmartTrack+ technology, it delivers accurate information on the status of sensitive structures to detect and react, even under the harshest conditions.



Versatile and customisable

The GM30 is ready to be customised for any monitoring scenario, from long-term static to dynamic high-frequency monitoring. It is easily combined with a variety of external devices and seamlessly connected with Leica Spider and Leica GeoMoS. In addition, the onboard data logging provides a direct connection with the Leica CrossCheck service.

Leica GM30

GNSS TECHNOLOGY

Leica Smart Track+ Very low noise GNSS carrier phase measurements (<0.5 mm rms). Signal acquisition < 30 s¹. Industry leading Pulse Aperture Correlator (PAC) multipath mitigation technology for superior quality measurements. Advanced radio frequency power spectrum analysis and interference mitigation on all GNSS bands.

GNSS signals² GPS (L1C/A, L1C, L2P(Y), L2C, L5)³; GLONASS (L1, L2P, L2C, L3)³
Galileo (E1, E5a, E5b, AltBOC, E6)³; BeiDou (B1, B2, B3)⁴;
QZSS (L1C/A, L1C, L2C, L5)³; NavIC L5; SBAS³ (WAAS, EGNOS, GAGAN, MSAS);
Available as GPS + GLONASS L1 only receiver.

Number of channels 555 universal tracking channels

MEASUREMENT PERFORMANCE AND ACCURACY⁵

Code differential Hz: 0.25 m + 1 ppm / V: 0.5 m + 1 ppm

Site Monitor	RTK positioning modes:	Reference Station (smoothed)	Monitoring (instantaneous)	Network RTK (instantaneous)
	Single baseline (< 30 km):	Hz: 6 mm +1 ppm V: 10 mm +1 ppm	Hz: 8 mm +1 ppm V: 15 mm +1 ppm	Hz: 8 mm +1 ppm V: 15 mm +1 ppm
	Network RTK:	Hz: 6 mm +1 ppm V: 10 mm +1 ppm	Hz: 8 mm +1 ppm V: 15 mm +1 ppm	Hz: 8 mm +1 ppm V: 15 mm +1 ppm

Time for initialisation (typical): 10s 10s 4s

VADASE (Velocity and displacement engine) Velocity accuracy: Hz: 0.003 m/s, V: 0.005 m/s
Typical velocity derived displacement sensitivity: Hz: 1 cm/s, V: 2 cm/s

PORTS AND CONNECTORS, COMMUNICATIONS

Ports PWR: Lemo-1 female, 5 pin
Serial P1: Lemo-1 female, 8 pin
GNSS antenna: TNC female
P3 slot-in antenna: TNC female
Oscillator: MMCX female, 24QMA-50 2-3/133, 5/10 MHz
Ethernet: RJ45 ruggedised, 10/100 Mbit
USB client: Type Mini B

Slot-in communication interface Exchangeable radio/GSM/GPRS/UMTS devices supported. Automatic gateway routing provides backup of internet access for continuity of communications.

TECHNICAL AND ENVIRONMENTAL

Power supply Nominal 24 V DC, range 10.5 – 28 V DC.

Battery External. Can serve as primary power source or as UPS backup.

Power consumption 3.5 W typical, 24 V at 145 mA

Dimension / weight (with rubber bumpers) 220x200x94 mm / 1.67 kg

Temperature Operating: -40 to 65 °C, Storage: -40 to 80 °C

Humidity Up to 100% non-condensing.
Compliance with ISO9022-13-06, ISO9022-12-04 and MILSTD-810G - 507.5-I

Vibration Withstands strong vibration during operation. Compliance with ISO9022-36-08 and MIL-STD-810G - 514.6-Cat.24.

Drop Withstands 1 m drop onto hard surfaces.

Proof against water, sand and dust IP67 (IEC 60529) and MIL-STD-810G - 512.5-I
Dust tight. Protected against water jets. Waterproof up to 1 m temporary submersion.

GENERAL

User interface Web interface for full receiver control and status information.
ON/OFF Button. 1x Function button. 6x LED for power, memory, logging, RT out, RT in, position

Data logging Removable SD card up to 32 GB. 12 parallel logging sessions. Data rates up to 50 Hz.
RINEX 2.11/3.xx, Hatanaka and Leica MDB formats including Zip compression.

Data streaming Up to 20 parallel data streams with multiple connections. Data rates up to 50 Hz.
Supports Leica, Leica 4G, CMR, CMR+, RTCM v2.1/2.2/2.3/3.2, BINEX, NMEA 0183 V 2.20 and proprietary formats via TCP/IP, Ntrip and serial.

RefWorx Web and FTP services Full control and configuration of the receiver over a web browser through Ethernet, mobile internet, serial or USB. Integrated watchdog for maximum quality and uptime. Backup and restore feature. Detailed event log and onboard messaging service.
Ntrip server (source), Ntrip client and Ntrip caster functionality with unlimited number of mount points.
Secure access using HTTPS, SSL certificates, access management and port blocking.
FTP Server and FTP Client (push), Email notification, SNMP support.

Leica Active Assist Automatic on-site and real-time online support service.

¹ Hot start (typical). Cold start <40 s (typical).

² The tracking capability for a specific satellite system is based on publicly available information. For cases where public information is subject to change or not yet available Leica Geosystems cannot guarantee full compatibility.

³ Hardware ready for: GPS/QZSS L1C, GLONASS L5 CDMA, Galileo E6, QZSS L6 and SBAS L5 will be provided through future firmware upgrade.

⁴ Designed for BeiDou Phase 2, Phase 3 compatibility.

⁵ Measurement precision, accuracy in position and height, reliability and time for initialisation are dependent upon various factors including the number of satellites tracked, the observation time, the ephemeris accuracy, the atmospheric conditions, multipath and resolved ambiguities. Figures quoted are RMS (root mean square) and assume normal to favourable conditions.

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2016. 846066en - 07.18