

Leica Lino point lasers

Technical data sheet



Delivery package Leica Lino P3:

Art. No. 777 067

- Leica Lino P3
- Target plate for red lasers
- Magnetic multifunction adapter
- Alkaline batteries (type AA, 3 × 1.5V)
- Carrying case and pouch




Delivery package Leica Lino P5:

Art. No. 777 068

- Leica Lino P5
- Target plate for red lasers
- Magnetic multifunction adapter
- Alkaline batteries (type AA, 3 × 1.5V)
- Carrying case and pouch

Technical Data	Lino P3	Lino P5
Range*	up to 30 m	
Levelling accuracy	± 1 mm @ 5 m	
Self-levelling range	4° ± 0,5°	
Number of laser dots	3	5
Beam direction	up, down, forward	up, down, forward, right, left
Accuracy of plumb points @ 5 m	± 1,5 mm	
Laser type	635 nm, laser class 2	
Battery type	type AA 3 × 1,5 V	
Battery life	up to 18 hours (alkaline)	
Protection class	IP 54	
Operating temperature	-10°C to 40°C	
Dimensions (H × D × W)	99,1 × 108,1 × 59,3 mm	
Weight with batteries	380 g	390 g
Tripod thread	1/4"	

*) depending on lighting conditions



Laser class 2 in accordance with IEC 60825-1

- when it has to be **right**

Leica
Geosystems