

Leica Zeno GG02plus GNSS/GIS SmartAntenna Datasheet



Reliable and accurate GNSS technology

The Leica Zeno GG02plus is a flexible GNSS receiver with cm accuracy – both real-time and post-processed. The Leica Zeno GG02plus combines a high-performance GNSS SmartAntenna with maximum simplicity for the data collection market.

- Built on years of knowledge and experience
- 72 L1/L2 GPS/GLONASS channels for optimum tracking behaviour in all environments. The GLONASS option improves the ability to track enough satellites in obstructed environments
- Delivers accurate and reliable results in the networks

Built for the field

Designed for the extreme environments – accurate, reliable and light-weight.

- With IP67 it is built to withstand the most demanding field environments but nevertheless light-weight and compact design
- Built to operate in extreme temperatures
- Easily exchangeable all-day-battery

Designed for versatile use

Choose the field computer, the field software and the setup (pole or backpack) to suit your workflow and budget.

- Ready-to-use with Leica Zeno Field, Leica MobileMatriX
- Ready-to-use with various Leica Geosystems handhelds and tablet computers such as Leica Zeno 10 & Zeno 15, Leica CS10 GIS & CS15 GIS and the Leica CS25
- Use Leica Zeno Connect to embed custom applications into Leica CS25, Leica Zeno 10 or Zeno 15

- when it has to be **right**

Leica
Geosystems

Technical Specifications

Leica Zeno GG02plus

GNSS technology	
Channels	72 channels
Satellite signals tracking	GPS: L1, L2, L2C (C/A, P, C Code) Optional: GLONASS: L1, L2 (C/A, P narrow Code)
Integrated Real-Time	SBAS (WAAS, EGNOS, MSAS) ³
Real-Time and Post-processed	Support of real-time correction service and post-processing to achieve cm positioning accuracy ¹
Output Data Protocols	NMEA-0183 (GGA, VTG, GLL, GSA, ZDA, GSV, RMC, GST, GRS) via Zeno Control only
Real-Time Protocols	RTCM 2.x, RTCM 3.0, CMR, CMR+
Update Rate	1 Hz
Post-Processed Accuracy ¹	Baseline mode L1 Phase: 10 mm + 2 ppm RMS
Horizontal Real-Time Accuracy ¹ (SBAS or external source)	SBAS < 1.2 m, RTK < 1 cm + 2 ppm
Vertical Real-Time Accuracy ¹	RTK < 2 cm + 2 ppm
Time for initialisation ²	Typically 8 sec
GG02plus SmartAntenna	
User Interface	On/Off key Status indicator (LED): Satellite tracking, Bluetooth® communication & battery power
Communication port	Bluetooth® 2.0 class 2 & sealed and protected 8-pin Lemo combined USB / power port
Field controller connection	By Bluetooth® or with GEV162 RS232 cable
Power Management	
Removable Battery	GEB211 (7.4 V / 2100 mAh Li-Ion rechargeable) or GEB212 (7.4 V / 2600 mAh Li-Ion rechargeable)
Battery Charging Time	2 hours to full charge with GKL211
Power	Nominal 12 V DC Range 10.5 – 28 V DC
Operating Time	7 h ⁶
Physical Specifications	
Weight	1 kg with all-day battery 2.8 kg ready-to-use with Leica CS10 GIS, pole and batteries
Environmental specifications	IP67: dust and water-resistant for all conditions Temporary submersion into water (max. depth: 1 m) Protected against blowing rain and dust
Operating / Storage temperature range ⁴	Operation: -40 to 65 °C Storage: -40 to 80 °C
Humidity	100%, non-condensing ⁵
Drop	Withstands topple over from a 2m survey pole onto hard surface Withstands 1 m drop onto hard surface
Vibration	Withstands vibration in compliance with ISO9022-26-08
Functional shock	No loss of lock to satellite signals when used on a pole setup and submitted to pole bumps up to 150 mm
Accessories and Optional Features	
Accessories	<ul style="list-style-type: none"> • External battery charger • Backpack kit • Hard carry case • 2 meter range pole
Optional Field and Office Software	<ul style="list-style-type: none"> • Leica Zeno Field • Leica MobileMatriX • Leica Zeno Connect • Leica Zeno Office and Leica Zeno Office on ArcGIS
Optional field computers	<ul style="list-style-type: none"> • Leica CS25 rugged Tablet Computer • Leica Zeno 10 and Zeno 15 GNSS/GIS handhelds • Leica CS10 GIS and CS15 GIS field controllers

¹ Measurement precision, accuracy and reliability depends upon various factors including number of available sat, geometry proximity to base station, multipath effects, ionospheric conditions etc.

² May vary due to atmospheric conditions, multipath, obstructions, signal geometry and number of tracked satellites.

³ WAAS available in North America only, EGNOS available in Europe only, and MSAS available in Japan only

⁴ Compliance with ISO9022-10-8, ISO9022-11-special and MIL-STD-810F Method 502.4-II, MIL-STD-810F method 501.4-II

⁵ Compliance with ISO9022-13-6, ISO9022-12-04 and MIL-STD-810F Method 507.4-I

⁶ May vary with temperature, battery age etc.



Total Quality Management – our commitment to total customer satisfaction.

The Bluetooth® word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Leica Geosystems AG is under license.

Other trademark and trade names are those of their respective owners.

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2011. 78893enUS – II.11 – RDV

Leica Geosystems AG
Heerbrugg, Switzerland

www.leica-geosystems.com

- when it has to be **right**

